



PVC-Packband PVC-Packaging-Tape

Beschreibung

Die Sorte 820 besteht aus einer glatten, reiß- und einreißfesten Hart-PVC-Folie, schmiegsam und zäh in Längs- und Querrichtung, die einseitig mit einem aggressiven, auch bei niedrigen Temperaturen gut haftenden Kleber beschichtet ist. Das Klebeband ist wasserdicht und beständig gegen Feuchtigkeit, verdünnte Laugen und Säuren.

Anwendung

Die Sorte 820 wird hauptsächlich als Verpackungsklebeband, aber auch vielseitig für technische Zwecke eingesetzt. Es klebt hervorragend auf allen Kartonoberflächen.

Technische Daten

Träger	Hart-PVC-Folie
Trägerdicke	32 µ
Gesamtdicke	52 µ
Dehnung bis Bruch	90 %
Klebkraft auf Stahl	2 N/cm
Zugfestigkeit	35 N/cm
Klebstoff	Naturkautschuk
Temperaturbeständigkeit	bis 60° C
Kerndurchmesser	76 mm
Farbe	transparent, braun
Länge	66 m

Verpackungseinheiten

Bandbreite in mm	Rollen pro Karton
50	36

Product Description

Type 820 consists of a smooth, tear proof HD-PVC-foil, that is length- and crosswise flexible and tough. It is coated one side with an aggressive glue, that adheres even at low temperature. The tape is waterproof and resistant against moisture, thinned bases and acids.

Application

Type 820 is mainly used as packaging tape, but is also versatilely usable in technical applications. It adheres excellently on any kind of carton surface.

Technical Data

Backing	HD-PVC-foil
Carrier thickness	32 µ
Total thickness	52 µ
Elongation at break	90 %
Adhesion on steel	2 N/cm
Tensile strength	35 N/cm
Adhesive	natural rubber
Temperature resistance	up to 60° C
Core diameter	76 mm
Colour	transparent, brown
Length	66 m

Packaging

Roll width mm	Rolls per carton
50	36

The information is based on our current knowledge and experience. No guarantee of specific properties or the suitability of the product for a particular purpose can be inferred from our information. All descriptions, drawings, photographs, data, ratios, weights, etc. contained herein are subject to change without notice and do not constitute the contractually agreed quality of the product. Technical changes, dimensional changes, printing errors, and mistakes are reserved.